

Your professional mounting solution –

used by international galleries, sign makers, industrial manufacturers, and many others ...

For decades, Neschen's gudy® mounting films have been a high-quality solution for a variety of customer demands. From high-end mounting of photos and prints, to point-of-sale advertising or industrial applications: gudy® mounting films create outstanding results.

The gudy® portfolio is made for cold lamination, guaranteeing best results after laminating with a laminating machine or by hand.



A professional mounting and framing solution for photographs, fine art prints, Baryte photo papers, photo albums, or passepartouts. From face mountings of ink jet papers behind acrylic glass or the high-end adhesion of fine art papers to board materials, the gudy® range is the best choice for our customers' demands.



Discover permanent or non-permanent adhesives for a variety of short-term or long-term applications, such as installing **promotional posters on shop windows, advertising on exhibition booths, or creating self-adhesive boards**. gudy® sets no boundaries to your creativity.



Dimensionally stable, flexible, and aging-resistant, the gudy® portfolio is a reliable, high-quality choice for many applications. The water-based adhesive formulations, with low or high adhesive strength, are environmentally friendly and ideal for **industrial applications like die manufacturing, the automotive industry**, and much more.

NESCHEN COATING GMBH
Hans-Neschen-Str. 1
31675 Bückeberg, Germany

T +49 (0)5722 207 0
E info@neschen.de

www.neschen.com

08/23

**GUDY®
PRODUCT OVERVIEW**



WWW.NESCHEN.COM



WWW.NESCHEN.COM

GUDY® PRODUCT OVERVIEW

	PERMANENT ADHESIVE									
	802	802 twin	8020 twin	803 power-tack	808 PP opaque	PP clear	831 Fine Art smooth	832 Fine Art textured	870	806 hybrid
Maximum width	160 cm	160 cm	200 cm	160 cm	160 cm	160 cm	160 cm	160 cm	124 cm	130 cm
Carrier type	PET	PET	PET	PET	white PET	OPP	paper	paper	carrier less	PVC
Thickness	23 µm	23 µm	12 µm	23 µm	75 µm	25 µm	44 µm	44 µm	carrier less	70 µm
Release liner	single-sided	double-sided	double-sided	single-sided	single-sided	single-sided	single-sided	single-sided	single-sided	single-sided
Primary bond	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent
Secondary bond	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent	semi-permanent
Adhesion power	medium	medium	medium	very high	medium	medium	high	high	medium	P - high / R - low
Recommended laminator speed	1-1,5 mpm	1-1,5 mpm	1-1,5 mpm	1-1,5 mpm	1-1,5 mpm	1-1,5 mpm	0,5-1 mpm	0,5-1 mpm	0,5 mpm	1-1,5 mpm
Indoor suitability	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Outdoor suitability	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Certificates	Photographic Activity Test (PAT) ISO 18916					Photographic Activity Test (PAT) ISO 18916	Photographic Activity Test (PAT) ISO 18916	Photographic Activity Test (PAT) ISO 18916	Photographic Activity Test (PAT) ISO 18916	

Recommended board applications

On acrylic plates	✓	✓	✓		✓	✓			✓	✓
Glass	✓	✓	✓		✓	✓			✓	✓
PVC hardfoam boards (e.g. Forex)	✓	✓	✓	✓	✓		✓	✓		✓
HPL boards	✓	✓	✓	✓	✓					
Polystrol boards (e.g. Smart-X)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Kapa boards	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dibond boards	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dark foamboards					✓		✓	✓		
Stadur boards (PVC-free)	✓	✓	✓	✓	✓	✓	✓	✓	✓	
MDF boards				✓				✓		
OSB boards				✓						
Veneer plates				✓				✓	✓	
Screen printing plates	✓	✓	✓	✓	✓					
Plywood boards				✓				✓		
Honeycomb paperboard	✓	✓	✓	✓			✓	✓	✓	✓

Suitable print media

PE or baryte photo paper	✓	✓	✓		✓	✓			✓	
Digital prints	✓	✓	✓	✓	✓	✓				✓
100% rag and alpha cellulose paper							✓	✓	✓	
Fine art papers smooth up to 300 g/m²							✓		✓	
Fine art papers textured up to 350 g/m²								✓		
Fine art papers >350 g/m²								✓		
Low-cost graphic papers up to 170 g/m²										✓
Textiles				✓						✓
Banner materials				✓						✓

Suitable Neschen laminating machines

Neschen PhotoLam 650	✓	✓					✓	✓		
Neschen EcoLam 1650	✓	✓		✓	✓	✓	✓	✓	✓	✓
Neschen ColdLam 1650	✓	✓		✓	✓	✓	✓	✓	✓	✓
Neschen HotLam 1650 TH	✓	✓		✓	✓	✓	✓	✓	✓	✓
Neschen HotLam 1650 DoubleH	✓	✓		✓	✓	✓	✓	✓	✓	✓

	NON-PERMANENT ADHESIVE		
	window	804	dot
Maximum width	130 cm	130 cm	160 cm
Carrier type	PET	PVC	carrier less
Thickness	23 µm	70 µm	carrier less
Release liner	double-sided	double-sided	single-sided
Primary bond	permanent	permanent	semi-permanent
Secondary bond	removable	removable	semi-permanent
Adhesion power	P - high / R - low	P - high / R - low	low
Recommended laminator speed	0,5 - 1 mpm	0,5 - 1 mpm	0,5 mpm
Indoor suitability	✓	✓	✓
Outdoor suitability			
Certificates			Photographic Activity Test (PAT) ISO 18916

Recommended board applications

On acrylic plates			✓
Glass	✓	✓	✓
PVC hardfoam boards (e.g. Forex)			✓
HPL boards			
Polystrol boards (e.g. Smart-X)			
Kapa boards			
Dibond boards			
Dark foamboards			
Stadur boards (PVC-free)			
MDF boards			
OSB boards			
Veneer plates			
Screen printing plates			
Plywood boards			
Honeycomb paperboard			

Suitable print media

PE or baryte photo paper	✓	✓	
Digital prints			
100% rag and alpha cellulose paper			
Fine art papers smooth up to 300 g/m²			✓
Fine art papers textured up to 350 g/m²			
Fine art papers >350 g/m²			
Low-cost graphic papers up to 170 g/m²			
Textiles			
Banner materials			

Suitable Neschen laminating machines

Neschen PhotoLam 650			
Neschen EcoLam 1650	✓	✓	✓
Neschen ColdLam 1650	✓	✓	✓
Neschen HotLam 1650 TH	✓	✓	✓
Neschen HotLam 1650 DoubleH	✓	✓	✓